Flashback 2 firmware upgrade 1.1.00 R880

This document describes the firmware upgrade procedure for the TC electronic Flashback 2 delay pedal

What's new?

- Support for new MASH calibration procedure (calibrate from Idle → see **MASH switch calibration tool guide PDF** for more infos)

Where do I find the firmware updater?

- firmware installers for MAC and PC are included in this .zip file

Preparing the firmware update

1. Download the latest firmware installer for your computer platform

2. Unplug all cables (including the power supply) from your TC pedal.

3. Connect the pedal to your computer using a USB cable.

4. Press and hold the footswitch on your Flashback 2 pedal

5. Insert the DC power supply plug **while keeping the switch pressed**. The LED on your pedal should turn green indicating that it is now in boot mode and ready to receive the firmware update.

6. Release the footswitch.

7. Start the firmware installer for your computer platform. You should be able to read "**Flashback 2 boot**" under device status

Once the pedal is in boot mode and you can read "**Flashback 2 Boot**" under **Device** status, press the update button to start the firmware upload

8. Press the green "**update**" button to start the firmware upload

Now that the firmware upload is in progress, no more interaction is needed.

9. Wait until the progress bar reads 100% and status parameter: **upgrade completed**

The pedal will auto-boot and is ready to use.

To re-calibrate the pedal, please refer to the **MASH switch calibration tool guide PDF document included in this download**