



LAYERS	
TOP ASSEMBLY	<input type="checkbox"/>
SILKSCREEN	<input checked="" type="checkbox"/>
SOLDERMASK	<input type="checkbox"/>
ROUTE	<input checked="" type="checkbox"/>
BOT ROUTE	<input type="checkbox"/>
SOLDERMASK	<input type="checkbox"/>
SILKSCREEN	<input type="checkbox"/>

BUILD-UP	Y(es)	N(o)	Notes:
TOP SILKSCREEN:	Y		
TOP SOLDERMASK:	Y		GREEN
TOP COPPER:	Y		35u
CORE			
BOT COPPER:	Y		35u
BOT SOLDERMASK:	Y		GREEN
BOT SILKSCREEN:		N	
LAMINATE:	FR4, DUAL SIDE		
TOTAL THICKNESS:	1,6mm +0.2mm / -0.1mm		
FINISH:	HAL		
COMPLIANCE:	UL94V-0, RoHS		

EDITION	DESCRIPTION				ECR
B	Added: C235-237, P208 and fiducial marks. PCB size increased from 128 to 130mm.				2587
CHANGED BY	2006-11-17/JBO		B	Z	
DATE/CORR.	2006-11-17/JBO				
CONTR./APPR.	JBO/JM	LSK	AL		
DESIGNED	DRAWN	CONTR.	APPR.	PROD.	OLD DRAWING NO.
JBO 2006/09/19	JBO 2006/09/19	JBO / JM	LSK	AL	LD24501D.pcb
SUBJECT				DRAWING NO.	SCALE
Project 492 / Power amplifier				451 476 02	1 : 1
EDITION				SIZE	
B				A4	
FILENAME 45147602B.pcb					