



LM26

Part list

LAB.GRUPPEN

For safety critical components please contact Labgruppen for the right manufacturer							
Item number	Safety critical	Item name	Replaces	Designator	Service level		
Power supply		See restriction nr3 on how to find our item names			1	2	3
SP04		Switch Mode Power Supply 0.04kW					x

Mainboard							
LP26A88D-07A-T		LP26A88D-07A-T FCT		Replaces all LP26A88D-XXX Please make sure that you also give us the serial number together with the order to be able to program your board			x
LM4562MA		Ic Operational Amplifier LM4562MA SOIC-8		U16, U17, U18, U20, U21, U31, U32, U33, U34, U93, U94			x
1606Q16-U		IC balanced line driver 1606Q16-U QSOP-16		U8, , U9, U11, U12, U13, U14,			x
PCDPCO1A3VSMD		Relay PCB Double Pole Change Over 1A 3V Surfacedmounted		K5, K6, K7, K8, K9, K10			x
NE8FBH-LED		Connector Ethercon Female+jack 90dg, metal housing+led pipes		J3, J4			x
TPS40057		Ic Buck Controller TPS40057 HTSOP-16		U39, U72, U83			x
CS4398		Ic D/A Converter CS4398 TSSOP-28		U46, U95, U701			x
SP8K4FU6		Transistor Mosfet SP8K4FU6 SOIC-8		U24, U73, U82, U87			x

LM26

Part list

LAB.GRUPPEN

1K0.063W1%0603		Resistor 1K0 .063W 1% Surface Mounted 0603						x
----------------	--	--	--	--	--	--	--	---

User interface								
UID128X64P		UID128X64P /User Interface Display 128X64 pixels						x
FS56x41x2		Foam Sticker 56x41x2mm						x
UID603b-LM26		User Interface Display 6ch rev.03b assembled for LM 26						x
ACUIB		Acryl cover userinterface Type B						x
FFCP.5C24L152D		Flat Flex Cable Pitch 0.5mm Cond 24 Length 152mm type D						x

Chassis								
CH1UA-PBLK		Chassis 1 Unit type A Painted Black						x
TC1UA-PBLK		Top Cover 1 Unit type A Painted Black						x
EFPP-PBLK		Exterior Front Panel Type F Painted Black						

Miscellaneous								
F40x28-24		Fan 40x40x28mm 24vdc						x
SRPLM26		Sticker Rear Panel LM 26				X		
SCAFCCMBGC		Sticker Caution Approvals FCC Must Be Grounded Type C						x
MLEU10ACEE7-C13L		Mains Lead Grounded Eu 10A Plug Cee7/vii + Con. C13 Lockable				X		

LM26

Part list

LAB.GRUPPEN

MLUS10A5-15-C13L		Mains Lead Grounded US 10A Plug Nema5-15p+ Con. C13 Lockable			x		
QSG-LM		Quick Start and Field Reference Guide for LM Series			X		
EC12E2420803		Rotary Encoder EC12 24PPR 30mm Shaft					x
DSSU440x5DSUB		Distansskruv Stål UNC4/40 x5mm for D-SUB					X
DF81x21x6.5-20		Dustfilter 81x21x6.5mm 20ppi Filtren Firend (a) V-0 Hf1					X
CAD25P-4M4FXLR1M		Cable assembly D-sub 25pole to 4 Male, 4 Female XLR, 1 meter					x
NC3FBH2		Connector Xlr 3pole Female 90dg, Metal Housing					x
PEPPC1UB		Packing EPP Corner 1 Unit type B			X		
B1UA-LMS		Box 1Unit type A 529x456x84mm 4col print LAKE LM series			X		